

SOĞUTMA TESİSATI BORU ÇAPLARI

(7 - 12 °C İÇİN)

ISITMA TESİSATI BORU ÇAPLARI

(40 - 50 °C İÇİN)

ISITMA TESİSATI BORU ÇAPLARI

(90 - 70 °C İÇİN)

Alt Limit	Üst Limit	BORU ÇAPI	
		DN	Inch
0,00	2,90	DN 15	1/2"
2,91	5,81	DN 20	3/4"
5,82	11,62	DN 25	1"
11,63	24,70	DN 32	1 1/4"
24,71	36,33	DN 40	1 1/2"
36,34	63,95	DN 50	2"
63,96	116,27	DN 65	2 1/2"
116,97	218,02	DN 80	3"
218,03	377,90	DN 100	4"
377,91	654,06	DN 125	5"
654,07	1.061,04	DN 150	6"
1.061,05	2.034,88	DN 200	8"
2.034,89	3.197,67	DN 250	10"
3.197,68	4.796,51	DN 300	12"
4.796,51	5.813,95	DN 350	14"
5.813,96	7.267,44	DN 400	16"
7.267,45	9.302,32	DN 450	18"
9.302,33	11.627,90	DN 500	20"

Alt Limit	Üst Limit	BORU ÇAPI	
		DN	Inch
0,00	1,20	DN 15	1/2"
1,20	3,50	DN 20	3/4"
3,50	7,00	DN 25	1"
7,00	14,00	DN 32	1 1/4"
14,00	23,30	DN 40	1 1/2"
23,30	43,60	DN 50	2"
43,60	93,00	DN 65	2 1/2"
93,00	157,00	DN 80	3"
157,00	261,60	DN 100	4"
261,60	407,00	DN 125	5"
407,00	697,70	DN 150	6"
697,70	1.453,50	DN 200	8"
1.453,50	3.488,40	DN 250	10"

Alt Limit	Üst Limit	BORU ÇAPI	
		DN	Inch
0,00	3,48	DN 15	1/2"
3,49	8,13	DN 20	3/4"
8,14	17,44	DN 25	1"
17,45	29,06	DN 32	1 1/4"
29,07	46,51	DN 40	1 1/2"
46,52	93,02	DN 50	2"
93,03	174,41	DN 65	2 1/2"
174,42	290,69	DN 80	3"
290,70	523,25	DN 100	4"
523,26	872,09	DN 125	5"
872,10	1.453,48	DN 150	6"
1.453,49	3.197,67	DN 200	8"
3.197,68	4.883,72	DN 250	10"